

Dalian Evershine International Trade Co., Ltd.

Add: No. 69 Qiyi Street, Zhongshan District, Dalian, China.

Tel: +86 411 82642906 Cell: +86 136 0428 6148

E-mail: <u>helen.guan@chinaevershine.com</u>

www.chinaevershine.com

Slewing Bearings

1. Photo:



2. Category:

- Four-point contact ball slewing bearing
- Double-row four-point contact ball bearing
- · Crossed cylindrical roller slewing bearing
- · Crossed tapered roller slewing bearing
- Three-row cylindrical roller slewing bearing

3. Specification:

The dimension range of slewing bearings that we can manufacture is inner diameter \geq 80mm, and outer diameter \leq 6070mm.

4. Cages:

The cages of DES slewing bearings have different structures such as whole type, sectional type and separate type. Among which cages of whole type and sectional type are made of #20 steel or ZL102 aluminum casting alloys. Cages of separate type are made of polyamide resin 1010 ZL102 aluminum casting alloy or QA110-3-1.5 aluminum bronze. In present years with the development of material industry, Nylon GRPA66.25 is also widely used to produce sectional cages.

5. Applications:

Slewing bearings are widely used in the slewer of Hoisting and Conveying Machinery, mining machines, constructional machines, harbour machines, wind power generation machines, armarium, radar and missile launcher.